



Bauform	T <sub>KN</sub> <sup>1)</sup> [Nm]	Leerlaufdrehzahlen		D <sub>1</sub> <sup>+0.008 -0.005</sup> [mm]	D <sub>2</sub> ±0,013 [mm]	Klemmspalt- höhe [mm]	e <sub>min</sub> [mm]	D <sub>min</sub> [mm]	d <sub>max</sub> [mm]	Brems- bügel Anzahl	Klemm- körper Anzahl	Gewicht [kg]
		n <sub>l max</sub> <sup>2)</sup> [min <sup>-1</sup> ]	n <sub>a max</sub> <sup>3)</sup> [min <sup>-1</sup> ]									
DC2222G	63	8600	4300	22,225	38,885	8,33 ±0,1	10,0	50	15	-	12	0,030
DC2776	119	6900	3400	27,762	44,422	8,33 ±0,1	13,5	58	18	-	14	0,055
DC3034	124	6300	3100	30,340	47,000	8,33 ±0,1	13,5	62	20	-	14	0,060
DC3175(3C)	159	6000	3000	31,750	48,410	8,33 ±0,1	13,5	63	21	3	16	0,060
DC3809A	275	5000	2500	38,092	54,752	8,33 ±0,1	16,0	71	25	-	18	0,085
DC4127(3C)	224	4600	2300	41,275	57,935	8,33 ±0,1	13,5	75	27	3	18	0,090
DC4445A	363	4300	2100	44,450	61,110	8,33 ±0,1	16,0	79	29	-	20	0,095
DC4972(4C)	306	3800	1900	49,721	66,381	8,33 ±0,1	13,5	86	33	4	22	0,100
DC5476A	525	3500	1700	54,765	71,425	8,33 ±0,1	16,0	92	36	-	24	0,110
DC5476A(4C)	525	3500	1700	54,765	71,425	8,33 ±0,1	16,0	92	36	4	24	0,130
DC5476B(4C)	769	3500	1700	54,765	71,425	8,33 ±0,1	21,0	92	36	4	24	0,180
DC5476C(4C)	990	3500	1700	54,765	71,425	8,33 ±0,1	25,4	92	36	4	24	0,200
DC5776A	604	3300	1600	57,760	74,420	8,33 ±0,1	16,0	98	38	-	26	0,110
DC6334B	806	3000	1500	63,340	80,000	8,33 ±0,1	21,0	104	42	-	26	0,175
DC7221(5C)	675	2600	1300	72,217	88,877	8,33 ±0,1	13,5	115	48	5	30	0,140
DC7221B	1279	2600	1300	72,217	88,877	8,33 ±0,1	21,0	115	48	-	30	0,185
DC7221B(5C)	1279	2600	1300	72,217	88,877	8,33 ±0,1	21,0	115	48	5	30	0,210
DC7969C(5C)	2038	2400	1200	79,698	96,358	8,33 ±0,1	25,4	124	53	5	34	0,280
DC8334C	2055	2300	1100	83,340	100,000	8,33 ±0,1	25,4	132	55	-	34	0,270
DC8729A	1250	2200	1100	87,290	103,960	8,33 ±0,1	16,0	134	58	-	34	0,165
DC10323A(5C)*	1612	1800	900	103,231**	119,891	8,33 ±0,1	16,0	155	68	5	40	0,205
DC12334C*	4800	1500	750	123,340**	140,000	8,33 ±0,1	25,4	184	80	-	50	0,400
DC12388C(11C)	4875	1500	750	123,881	142,880	9,50 ±0,1	25,4	186	80	11	44	0,400

1) T<sub>max</sub> = 2 x T<sub>KN</sub>

2) Innenring überholt

3) Außenring überholt

\*) Die Zentrierflanke des Innenkäfigs liegt gegenüber

\*\*) Toleranzerweiterung ±0,013 zulässig

weitere Abmessungen auf Anfrage

Bestellbeispiel : Freilauf DC7221B(5C)

Maß- und Konstruktionsänderungen vorbehalten